



## ITONA TI 5621

# Thin Client

Networking Ideas  
..... Thin Solutions



Itona TI is available with a variety of operating systems (Gio Linux, Mozilla, Microsoft Windows CE and Microsoft Windows XP Embedded) so it connects easily to a wide range of servers and networks. With integrated 54Mbps wireless LAN and 10/100 Ethernet, Itona TI delivers the security and central manageability of thin client computing – in a package.

Itona TI gives you all the advantages of thin client computing with integrated LCD Panel.



Itona TI 56xx series

### About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide – with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters is in Bangalore, India.

### Fully featured

With an extensive range of ports (USB x4, PS/2 x2, audio, headphone, 10/100 Ethernet, wireless LAN, VGA out and serial port), 32-bit graphics display and Itona TI has got pretty much everything you need. If you want more, you'll be pleased to hear that RAM can be upgraded to 1Gb – and Flash memory to 4Gb.

### Secure mobile computing

Central data storage, remote management software and workstation-class security – in a device.

### Choice. Choice. And choice.

Itona comes in a range of configurations, so you can be sure that there's an ideal Itona for your network.

### Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

# ITONA TI 5621

## Thin Client



### Modular Terminal

Based on the Microsoft Windows XP Embedded operating system  
Standard Client Software:  
Citrix ICA, Integrated Microsoft RDP, Internet Explorer, terminal emulation protocols standard.

### Hardware

**RAM** : 512 MB Upgradable upto 1 GB

**Flash** : 512 MB Upgradable upto 4 GB

**Processor** : VIA C7 1000 MHz

#### Input/Output/Peripheral Support :

- 1 serial port
- PS/2 Mouse
- 4 USB 2.0 ports (2 at rear, 2 on the side)
- VGA video output (DB-15)
- PS/2 Keyboard
- Dual Channel LVDS interface
- Internal slim HDD (Optional)

#### Monitor ( In-built LCD Display Panel )

- 17" LCD Display
- 1280X1024 resolution
- Pixel Pitch 0.264x 0.264(mm<sup>2</sup>)
- Luminance 260 cd/m<sup>2</sup>
- Dual Channel LVDS interface
- ELO 5-Wire resistive (Optional)
- USB Interface
- Point density 4096x4096

#### Networking

- Autosensing, 10/100 Ethernet, RJ-45
- Wake On Lan
- 802.11b+gWLAN
- PXE boot

#### Display Support

- Maximum resolution Up to 1280x1024
- Support two displays dual view
- Extended video support

#### Audio

- Line Out
- Mic

#### OPTIONS

- 1 x 2.5" HDD
- Smart Card Reader
- Mini PCI Card Slot

#### Physical Characteristics

- Unit: 42.5cm x 39 cm x 21 cm (vertical)
- Packing: 27cm x 56 cm x 50.5 cm

#### Ambient Temperature Range

- Temperature Range : Powered on: 32° to 104°F (0° to 40°C)
- Humidity : 20% to 80% noncondensing

### Software

#### Firmware Features :

- Microsoft Windows XPE
- Microsoft Internet Explorer 6.0 resident:
  - 1 HTML, JavaScript , XML, Active X,
- RDP 6.0 resident
- Citrix ICA 10.xx resident
- Terminal emulation emulates 60 terminal types.

#### Server OS Compatibility/Support :

- Microsoft Windows 2000/2003 Server
- Citrix Winframe and MetaFrame
- Microsoft Windows NT Server 4.0 Terminal Server Edition

#### Security:

- EWF Manager, User registry restrictions

#### PLUG-INS:

- Adobe Acrobat Reader, Macromedia Flash wave and Shock wave

#### Set-Up & Configuration:

##### User interface :

- Boot from local Flash
- Windows XP user interface language: U.S. English; French, German, Spanish optional
- Keyboard Language support: U.S. English standard; All other languages supported
- JAVA/JVM, VNC Shadowing
- VPN, Customizable Thinprint
- Smart Card Support,
- ELO Touch screen Support
- PPP / DIAL-UP- Networking
- USB Input Devices Support
- My ODBC Client Support

#### Protocol Support :

- TCP/IP, DNS, DHCP, PXE, RPL

#### Management

- Remote Management, configuration, and upgrades through XLManage software version 1.29 or later
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration ( IP information, name, etc.)
- Remote screen shadowing of entire desktop (VNC)
- Reporting

### Power

- External power Adpater 12 Volt 80 Watt.
- Worldwide auto-sesing 100-240 VAC., 50/60 Hz

### Regulatory Compliance

- UL & CE

### Warranty

One-year limited warranty



### VXL Instruments Limited

Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines)

Fax: +91 80 28520095

E-mail: sales@vxl.net

Web: www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55

Fax: +44 (0) 16 17 75 48 66

E-mail: peter.best@vxl.net

#### VXL Presence:

##### France

Tel. : +33 (0) 1 42 17 00 03

E-mail: pjaspard@vxl.net

##### Germany

Tel. : +49 (0) 8761 1093

E-mail: gerdb@vxl.net

##### United States

Tel. : +1 713 589 3273

E-mail: sales@vxl.net