



## Specifications

### Description

<b>Product Description</b>	USB to 1-port Parallel I Adapter
----------------------------	----------------------------------

### Parallel Communication

<b>No. og port</b>	1-port
<b>Mode</b>	SPP Mode (Support Printer only)
<b>Cable connectors</b>	DB25 Female
<b>ESD Protection for Parallel I/O</b>	±2KV Human Body Model (HBM)

### Driver Support

<b>Microsoft</b>	Microsoft Windows 98/ME/2000/XP/ 2003/Vista (32bit)
------------------	---

### Regulatory Approvals

<b>Hardware</b>	EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Part 15 Class B, RoHS
<b>Software</b>	Microsoft WHQL Window XP

### Environment

<b>Operating Temperature</b>	0 to 60°C (32 to 140°F)
<b>Operating Humidity</b>	5% to 95% RH
<b>Storage Temperature</b>	-20 to 85°C (-4 to 185°F)

### Power

<b>Input</b>	USB Bus-power
<b>Consumption</b>	< 1W = 5V x200mA

### Mechanical

<b>Dimension</b>	75 (W) x 40 (D) x 22 (H) mm
<b>Cable Length</b>	150mm (5ft)
<b>Case</b>	ABS
<b>Weight</b>	95 ± 5 g