

4070U (ISA)

2 Port RS-232 / 1 Port Parallel Card

no picture
available



■ Introduction

Sunix's 4070U is a serial and parallel combo expansion card. It offers you two ports of DB9M connection plus one port of parallel for all your project needs. The serial ports have a data transfer rate up to 921.6 Kbps and the parallel port offers speed up to 770 KB/sec. The card is ideal for project like the POS system, automation assembly, ISDN terminal, and more.

■ Features

- Support 16-bit PCI bus
- 5V connect key compatible
- Low repair rate with ASIC design
- Ideal for PC-based embedded systems
- Easy to install
- Serial
 - On-chip SUN1699 hardware flow control
 - Delivers fastest data transmission available, with speed up to 921.6 Kbps
 - Works perfectly with maior Operating Syatems
- Parallel
 - IEEE 1284C Standard Compatiable
 - Support ECP / EPP / BPP / SPP mode
 - Speed up to 2.7 MB/sec

■ Specifications

■ Function

TYPE	Sunix Multi I/O Communication Board	
Serial	Mode of Operation	Hand-Shaking
	Bus Transceivers	RS-232 full duplex
	Drivers per line	RS-232 1 driver
	Receivers per line	RS-232 1 receiver
Parallel	Mode of Operation	ECP / EPP / SPP / BPP

Hardware

Bus Interface		8-bit ISA bus
		5V connector keys
Dimension (WxD)		105 x 78 mm
Bracket		Standard 121 mm x 2 2
Serial	IC	SUN1699
	Controller	Sunix UART (16C650 compatible)
	No. of Ports	2 ports
	PCB Connector	DB9M port
Parallel	IC	SUN1689
	Controller	IEEE1284C standard compatible
	No. of Ports	1 port
	PCB Connector	Pin Head 13 x 2

Communication

Serial	Interrupter	IRQ 3/4/5/7/9
	I/O address	3F8, 2F8, 3E8, 2E8
	FIFO	32 byte hardware FIFO
	Baud Rate	75 bps ~ 921.6 Kbps
	Data bit	4,5,6,7,8
	Stop bit	1,1.5,2
	Parity	even, odd, none, mark, space
	Flow Control	None, Xon/Xoff, Hardware
	RS-232 Signal	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Parallel	Interrupter	IRQ 3/4/5/7/9/10
	I/O address	3BC, 378, 278
	FIFO	32 byte hardware FIFO
	Baud Rate	770 KB/sec

Regulator approvals

Hardware	CE, FCC
-----------------	---------

Driver support

Microsoft	Windows 9x, NT, 2000
Linux	2.0x / 2.2x
DOS	DOS

■ Operation Environment

Operation Temperature	0 °C ~ 57 °C
Operation Humidity	5 ~ 95% RH
Storage temperature	-20°C ~ 85°C

■ Package content

Hardware	Sunix 4070U Multi I/O Communication Card
Cable	Print Cable
CD	Driver CD
Manual	User Manual



Headquarter Germany:
SPHINX Computer Vertriebs GmbH
Phone: +49 (0) 6201 75437
www.sphinxcomputer.de
mail@sphinxcomputer.de

Subsidiary France:
SPHINX Connect France
Phone: +33 (0) 2 51 09 26 60
www.sphinxconnect.com
mail@sphinxconnect.com

Subsidiary Germany:
SPHINX Connect GmbH
Phone: +49 (0) 711 7287 5750
www.sphinxconnect.de
mail@sphinxconnect.de

Branch Office Belgium
Phone: +32 26 39 39 48
www.sphinxconnect.com
benelux@sphinxconnect.com

Subsidiary Austria:
S-Connect Vertriebs GmbH
Phone: +43 (1) 504 84 78 0
www.s-connect.at
mail@s-connect.at

Branch Office Spain
Phone: +34 913 109 823
www.s-connect-espana.com
mail@s-connect-espana.com

Subsidiary Great Britain:
S-Connect Ltd.
Phone: +44 (0) 1276 203 10
www.s-connect.ltd.uk
mail@s-connect.ltd.uk

Sales Partner Switzerland:
VISONET AG
Phone: +41 41 768 05 80
www.visonet.ch
info@visonet.ch