



UTS2009P

USB to RS-232 HUB



■ Introduction

Sunix's UTS2009P is an USB to RS-232 hub which offers user two serial port connections. The ports have a data transfer rate up to 115 Kbps. Users are able to connect two serial devices through the hub to the USB port on their system. The hub supports wake on line and power management function. It has dual data buffers for upstream and downstream data flow.

■ Features

- USB1.1 full speed 12Mbps with bus power
- USB 2.0 backward Compatible
- Support Wake on line & power manager function
- Support Hot-Swapping & Plug-n-Play
- No IRQ, DMA, I/O, address resources required
- Support RS-232 Automatic handshake mode
- Dual data buffers for upatream and downatream data flow
- RS-232 Speed up to 115Kbps
- Friendly Grapgic User Interface

■ Specifications

■Function

| | |
|---------------------------|---------------------------------------|
| TYPE | Sunix USB to Serial Communication HUB |
| Mode of Operation | Handshaking |
| Bus Transceivers | RS-232 Full-Duplex |
| Drivers per Line | RS-422 1 Driver |
| Receivers per Line | RS-232 1 Receivers |
| | RS-232 1 Receivers |

■Hardware

| | |
|--------------------------|-----------------------------------|
| IC | Prolific 2303HX |
| Controller | SUNIX UART (16C550 compatible) |
| No. of Ports | 7,4,2,1 ports |
| Connector | DB62F/DB9M/MiniBlock DC jacker |
| Bus Interface | Universal Serial Bus (USB) |
| Dimension (WxDxH) | 180 x 70 x 26 mm |
| Power | DC power 2 |

■Communication

| | |
|------------------------------|--|
| IRQ & I/O address | Assigned by BIOS |
| FIFO | 16 byte hardware FIFO |
| Baud Rate | 115Kbps |
| Data bit | 5,6,7,8 |
| Stop bit | 1, 1.5, 2 |
| Parity | even, odd, none, mark, space |
| Flow Control | None, Xon/Xoff, Hardware |
| RS-422 Singal | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND |

■Regulator approvals

| | |
|-----------------|---------|
| Hardware | CE, FCC |
| Software | WHQL |

■Driver support

| | |
|------------------|----------------------------|
| Microsoft | Windows 9x, 2000, XP, 2003 |
|------------------|----------------------------|

■Operation Environment

| | |
|------------------------------|--------------|
| Operation Temperature | 0°C ~ 57 °C |
| Operation Humidity | 5 ~ 95% RH |
| Storage temperature | -20°C ~ 85°C |

■Package content

| | |
|-----------------|---|
| Hardware | SunixUSB to Serial HUB Switch Adapter (Optional) |
| Cable | DB62M to 8/4 ports DB9M or DB25M USB MinA to B Cable |
| CD | Driver CD |
| Manual | User Manual |

Optional

| Item | Port | Function | | FIFO | Port Type | | | USB Interface | Power | |
|----------|------|-----------|--------|----------|-----------|-------|-----------|---------------|-------|----------|
| | | RS422/485 | RS-232 | Hardware | DB9M | DB25M | Mini Blok | | USB | External |
| UTS7009P | 7 | | • | 16 | • | • | | 2.0/1.1 | • | • |
| UTS4009P | 4 | | • | 16 | • | | | 2.0/1.1 | • | • |
| UTS2009P | 2 | | • | 16 | • | | | 2.0/1.1 | • | |
| UTS1009 | 1 | | • | 16 | • | | | 2.0/1.1 | • | |
| UTS1025 | 1 | | • | 16 | | • | | 2.0/1.1 | • | |



Headquarter Germany:
SPHINX Computer Vertriebs GmbH
 Phone: +49 (0) 6201 75437
www.sphinxcomputer.de
mail@sphinxcomputer.de

Subsidiary France:
SPHINX Connect France
 Phone: +33 (0) 2 51 09 26 60
www.sphinxconnect.com
mail@sphinxconnect.com

Subsidiary Germany:
SPHINX Connect GmbH
 Phone: +49 (0) 711 7287 5750
www.sphinxconnect.de
mail@sphinxconnect.de

Branch Office Belgium
 Phone: +32 26 39 39 48
www.sphinxconnect.com
benelux@sphinxconnect.com

Subsidiary Austria:
S-Connect Vertriebs GmbH
 Phone: +43 (1) 504 84 78 0
www.s-connect.at
mail@s-connect.at

Branch Office Spain
 Phone: +34 913 109 823
www.s-connect-espana.com
mail@s-connect-espana.com

Subsidiary Great Britain:
S-Connect Ltd.
 Phone: +44 (0) 1276 203 10
www.s-connect.ltd.uk
mail@s-connect.ltd.uk

Sales Partner Switzerland:
VISONET AG
 Phone: +41 41 768 05 80
www.visonet.ch
info@visonet.ch