1 to 4/8 CAT5 VGA + Audio Transmitter

Model No.: AV-702Z-114VA /118VA

1 Port Mini CAT5 VGA + Audio Receiver

Model No.: AV-701Z-S111

The 1-to-4/8 CAT5 AV Transmitter simultaneously broadcasts, in real-time, both stereo audio and video images to multiple remote screens at great distances via a single, easy installed CAT5 cable.

The Mini compact AV-701Z-S111 Receiver is a high value, affordable solution for receiving your VGA + Stereo Audio from AV-702Z-114VA/118VA Transmitter up to a distance of 150m/500ft away over clutter free CAT5/6/7 cables.

Features

- Extends high-resolution VGA signal and high fidelity stereo audio to remote displays.
- Easily distributes one audio & video source to 4/8 displays simultaneously.
- ❖ Supports up to 1920 x 1200 @ 60Hz resolution.
- Supports DDC for monitors.
- AV-701Z-S111 Receiver has Gain and EQ adjustments for optimum image quality.
- ❖ Pure hardware, Plug n Play design.
- Supports the latest LCD, VGA, SVGA, XVGA, SXGA and multi-sync monitors.

Specification

Model No.		AV-702Z-114VA	AV-702Z-118VA	AV-701Z-S111
System Cable		CAT5, FTP Solid Wire 2x4x24 AWG., Standard 568B RJ-45 connector		
Connectors	System Out: RJ-45	4	8	
	System In: RJ-45	-	_	1
	VGA In: HDD15F	1	1	-
	VGA Out: HDD15F	1	1	1
	Audio In: 3.5mm Jack	1 (Blue)	1 (Blue)	-
	Audio Out: 3.5mm Jack	1 (Green)	1 (Green)	1 (Green)
	Power In: Jack	1 (AC)	1 (AC)	1 (DC)
	Power LED	1 (Green)		
Distance		Depends on receiver, and on cable quality. 0~300M (0~1000 ft)		150 M (500 ft)
Video		1920 x 1200 @ 60Hz		
Power Consumption		100~240V AC IN		DC 5.0V;1.2A
Works with		AV-701Z-111/311/315 Receiver		AV-702Z-111/11 4VA/118VA Transmitter
	Operating Temp.	0~70°C		
Environm	Storage Temp.	-20~85°C		
Environin	Humidity	0-80% RH, Non-condensing		
	Housing	Metal		
Physica	Weight	860g (1.90 lb)		60g (2.1 oz.)
Properti		13.4 x 21.3 x 4.4 cm (5.28 x 8.38 x 1.73 in.)		7.3 x 5.3 x 2.25 cm (2.9 x 2.1 x 0.9 in)






Panel View



AV-701Z-S111



Diagram



Accessories

