


# Power Adaptors

The following power adaptors can be used with these products: NPort® DE-211/311, NPort® 5100/5200/5400/6150/6250/6450, NPort® W2004, NPort® 2150/2250 Plus, UC-7110/7410/7420, VPort 251



	PWR-12150-CN-S1	PWR-12120-USJP-S2	PWR-12120-DT-S2	PWR-12200-DT-S1	PWR-12042-US-S2	PWR-12042-EU-S1
<b>Input Rating</b>						
I/P	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz
<b>Input Plug</b>						
Plug Type	CN	US/JP	–	–	US	Euro
<b>Output Rating</b>						
O/P	1.5 A @ 12 VDC	1.2 A @ 12 VDC	1.2 A @ 12 VDC	2 A @ 12 VDC	420 mA @ 12 VDC	420 mA @ 12 VDC
<b>Output Plug</b>						
Connector Type	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.5	S-type 5.5/2.1/7.5	S-type 5.5/2.1/7.5	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0
Outer Diameter	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm
Inner Diameter	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm
<b>Physical Characteristics</b>						
Dimensions	70 x 45 x 54 mm	75 x 34 x 72 mm	80 x 49.5 x 30 mm	110.8 x 51.8 x 32 mm	62 x 29 x 66 mm	62 x 29 x 78 mm
Weight	200 g	130 g	124.5 g	200 g	85 g	90 g
Cord Length	1800 ± 200 mm	1830 to 1950 mm	1830 mm (min.)	1800 ± 200 mm	1830 ± 150 mm	1830 ± 150 mm
<b>Environmental Limits</b>						
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
<b>Regulatory Approvals</b>						
Safety	UL/PSE	UL/PSE	UL/CE/FCC/TÜV/PSE/SAA	UL/CE/FCC/GS/CCC	UL/FCC	CE/TÜV



	PWR-12042-UK-S1	PWR-12040-AU-S1	PWR-12120-AU-S2	PWR-12150-EU-S2	PWR-12150-UK-S2	PWR-12200-DT-S2
<b>Input Rating</b>						
I/P	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz
<b>Input Plug</b>						
Plug Type	Euro	AU	AU	Euro	UK	–
<b>Output Rating</b>						
O/P	420 mA @ 12 VDC	400 mA @ 12 VDC	1.2 A @ 12 VDC	1.5 A @ 12 VDC	1.5 A @ 12 VDC	2 A @ 12 VDC
<b>Output Plug</b>						
Connector Type	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0	L-type 5.5/2.1/7.5
Outer Diameter	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm
Inner Diameter	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm
<b>Physical Characteristics</b>						
Dimensions	65 x 48 x 72 mm	64.2 x 40.3 x 62.24 mm	75 x 41 x 64.94 mm	70 x 45 x 66.5 mm	70 x 45 x 60 mm	110 x 60 x 34 mm
Weight	105 g	93 g	150 g	200 g	200 g	200 g
Cord Length	1830 ± 150 mm	1500 ± 100 mm	1500 ± 100 mm	1800 ± 200 mm	1800 ± 200 mm	1800 ± 100 mm
<b>Environmental Limits</b>						
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
<b>Regulatory Approvals</b>						
Safety	CE	SAA	SAA/CE	FCC/ELT/PSE/CE	CE/GS/FCC/PSE/ETL	CE/GS/FCC/PSE/UL

# Power Cords

The following power cords can be used with these products: CN2510, CN2600 Series, NPort® 5600 Series, NPort® 6600 Series

## PWC-C13US-3B-183



**US Plug** (110 V)  
Thickness: 6.8 mm  
Max. Current: 10 A  
Length: 1830 mm

## PWC-C13EU-2B-183



**Euro Plug** (250 V)  
Thickness: 6.8 mm  
Max. Current: 10 A  
Length: 1830 mm

## PWC-C13UK-3B-183



**UK Plug** (250 V)  
Thickness: 6.8 mm  
Max. Current: 5 A  
Length: 1830 mm

## PWC-C13JP-3B-183



**Japan Plug** (125 V)  
Thickness: 7.0 mm  
Max. Current: 7 A  
Length: 1830 mm

## PWC-C13AU-3B-183



**AU Plug** (250 V)  
Thickness: 6.0 mm  
Max. Current: 10 A  
Length: 1830 mm

## PWC-C13CN-3B-183



**CN Plug** (250 V)  
Thickness: 6.0 mm  
Max. Current: 10 A  
Length: 1830 mm