

# VBOX-3611-POEX

Taiwan Patent No. M447854, M448011

Intel Gen6 Core i7-6600U CPU with 4 x POE Ports On-Board Computer

## Features

- Intel Core i7-6600U
- Wireless support LTE w/ SIM Card, WLAN, GPS Dead Reckoning, BT (Option)
- 4 x Power Over Ethernet (POE)
- Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage, RAID 0, 1, 5
- 1 x CAN Bus 2.0B (Optional)



## Introduction

The VBOX 3611 POEX On-Board Computer is powered by Intel® Gen 6 Core i7-6600U with 4x POE ports, wireless support LTE, 3.5G w/ Dual SIM cards (Auto-switch). Additionally, it supports 9V - 36V DC Power Input. It can be operated in extreme weather conditions (Operating temperature: -40°C ~ 70 °C) and is suitable for railway station management and license plate recognition (LPR).

The VBOX 3611 POEX On-Board Computer is designed for fleet management, mobile DVR, driver behavior record and in-vehicle digital signage. This technology enables us to offer a new in-vehicle component which can be applied as part of biometric systems and passenger information collection for user authentication purposes.

## Specifications

| System          |  |
|-----------------|--|
| CPU             | Intel Gen6 Core i7-6600U 2.6GHz up to 3.4GHz   |
|                 | Intel Gen 6 Core i5-6300U 2.4GHz up to 3.0GHz  |
|                 | Intel Gen6 Core i3-6100U 2.3GHz  |
|                 | Intel Gen6 Dual Core 3955U 2.0GHz  |
| Memory          | 2 x DDR4 2133 MHz SO-DIMM up to 32GB   |
| Chipset         | Intel 6th Generation Core SoC Processor  |
| LAN Chipset     | Intel I210-AT Gb/s Ethernet Controllers Onboard Support PXE and WOL                                |
| Audio           | Realtek ALC662 HD Codec Onboard  |
| Watchdog        | Watchdog Timer Support, Offer 1 – 255 Step   |
| TPM             | 2.0  |
| I/O             |  |
| Serial Port     | 3 x RS-232<br>(2 with RS-422/485 (Optional Max 4 x RS-232/422/485))                                |
| USB Port        | 2 x USB 3.0 Ports, 2 x USB 2.0 Ports   |
| LAN             | 4 x M12 X-Code for GbE POE (IEEE802.3AF 15.4W per port)  |
| Video Port      | 1 x DVI-I*, 1 x DP, 1, VGA (Support Triple Independent Display)                                    |
| DIO Port        | 4 In and 4 Out   |
| Audio           | 1 x Line-out and 1 x Mic-in (Line-in Optional)   |
| SIM Card Socket | 1 x SIM Card Socket Supported Onboard with eject<br>* Use only with Single Link DVI Cables.        |
| Graphics        |  |
| Graphics        | Intel® HD Graphics 520   |
|                 | DirectX Video Acceleration (DXVA) for Accelerating Video Processing - Full AVC/VC1/MPEG2 HW Decode |
|                 | Supports DirectX 11/10.1/10/9 and OpenGL 4.0   |
| Resolution      | Max Resolution (HDMI1.4) : 4096x2304@24Hz  |
|                 | Max Resolution (DP) : 4096x2304@60Hz   |

| Software             |  |
|----------------------|--|
| Operating System     | Win 10, Ubuntu 16.04 64bit   |
| Environmental        |  |
| Operating Temp.      | -40°C ~ 70°C, ambient w/ 0.6m/s airflow<br><b>Patent No. : M448011 - Thermal Cooling</b>                   |
| Storage Temp.        | -40°C ~ 80°C   |
| Relative Humidity    | 10% RH – 90% RH (non-condensing)   |
| Vibration (with SSD) | IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis<br>MIL-STD-810G, Method 514.6, Procedure I, Cat.4, Operating |
| Shock                | Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD           |
| Certifications       | CE, FCC Class A, E-13  |
| Storage              |  |
| Type                 | 2 x 2.5" Drive Bay for SATA Type HDD/SSD RAID 0, 1, 5<br>1 x mSATA   |
| Power Requirement    |  |
| Power Input          | 9V - 36V DC Power Input  |
| Power Protection     | Automatics Recovery Short Circuit Protection   |
| Power Mgmt.          | Vehicle Power Ignition for Variety Vehicle   |
| Power Off Control    | Power off Delay Time Setting by Software and BIOS  |
| Battery (UPS)        | Internal Battery Kit for 10 Mins Operating (Optional)<br><b>Patent No. : M447854 - Build-in Battery</b>    |
| Mechanical           |  |
| Construction         | Aluminum Alloy   |
| Mounting             | Supports Both of Wall-mount/VESA-mount   |
| Weight               | 1980 g (Barebone)  |
| Dimensions           | 250 x 150 x 55 mm  |

## Dimensions