

NITE-RW

Unmanaged Industrial Ethernet Switch RJ45
Fast Ethernet



Reliable, space-saving networking in the control cabinet with only 28 mm installation depth

- Flexible use with 24 VAC/VDC
- Minimal installation depth 28 mm
- Temperature range -40 to +70°C
- Polarity protection
- IP30 metal housing
- Inrush current limitation
- Stable wall mounting
- PROFINET suitable

Unmanaged Industrial Ethernet Switch RJ45

Fast Ethernet



With an installation depth of only 28 mm and a height of 105 mm, the Industrial Ethernet switches impress with their extremely flat and high-quality aluminium housing. The ultra-compact switches can be used in any control cabinet thanks to the 24 VAC/VDC power supply with inrush current limiting and reverse polarity protection. Due to the reduced footprint and the arrangement of all connections on the front, switch cabinets and cabling can be optimized to reduce the costs. The wall mounting brackets made of metal, ensure a firm and secure hold. Like all TERZ Industrial Ethernet switches, the flat NITE-RW are available in two frame forwarding variants and fully suitable for PROFINET applications.

General

Switch: IEEE802.3 Store and Forward; non-blocking wire speed

Auto-Negotiation, Auto-MDI-X, Auto-Polarity: Yes

Frame size: 1,522 Bytes

MAC table size: 2,000 addresses

Quality of Service: Yes – 4 priority queues

Energy Efficient Ethernet: No

Flow Control: No

PROFINET suitable: Yes

Port count (RJ45)	5	8	16
MTBF (SN 29500, Mio. h)	2,709	2,005	1,109

Frame Forwarding (Art.-No.)	xxxxx0	xxxxx1
LLDP, PTCP Delay 01:80:C2:00:00:0E	Forwarding	Blocking
RSTP BPDU 01:80:C2:00:00:00	Forwarding	Forwarding

Power supply / electronics

Nominal voltage: Vin 24 VAC 50/60 Hz / 24 VDC

Permitted voltage range 5,8 ports: 8 to 28 VAC / 9 to 36 VDC

Permitted voltage range 16 ports: 12 to 28 VAC / 9 to 36 VDC

Connection type: 3-pole pluggable, screw connector (+ - FE)

Wire cross-section: 0.75 to 2.5 mm² (AWG 20 to 13)

Supply circuit: SELV DIN 60950 (circuit breaker 10 A)

Inrush current limiter: Yes

Input fuse: Yes, Interrupting rating 50 A @ 125 VAC / VDC

Polarity protection: Yes

PCB Conformal Coating: No

Protection category: III

Isolation: 0.75 kVDC; Vin ⇄ Ethernet Ports | Vin ⇄ housing

Port count (RJ45)	5	8	16
Power usage (W) Min Max	@24VDC 0.4 0.9	0.4 1.2	1.9 2.4
	@24VAC 0.5 0.98	0.5 1.3	2.00 2.5
Input current (mA) Min Max	@24VDC 16 36	16 48	80 100
	@24VAC 32 75	32 96	130 167
Inrush current (A)	8 A I _{peak} (DC=40 µs, cold start)		

Mechanical properties

Housing material: Anodised aluminium, stainless steel

Mounting: M4 hole for wall mounting

IP Protection class (operation): IP30

Port count (RJ45)	5	8	16
Width (mm)	69	85	137
Height (mm)	105	105	105
Depth (mm)	28	28	28
Weight (g)	190	240	380

Ethernet Interfaces

IEEE Standards: 802.3 10BaseT, 802.3u 100BaseT(X)

Isolation: 0.75 kVDC; Ethernet Port ⇄ housing | Port ⇄ Port

Connection type: RJ45

Port Count | Speed: 5,8 Ports | 10/100 Mbit/s

Cable length: 100 m (Twisted Pair, 0.14 mm² - 0.22 mm², Cat 5)

EMC and environmental specifications

Operating temperature: -40°C to 70°C

Storage temperature: -40°C to 85°C

Relative humidity (operation): 0%-95% (not condensing)

Relative humidity (storage): 0%-95% (not condensing)

Atmospheric pressure (operation): 2,000 m (795 hPa)

EMC immunity: DIN EN - 61000-6-2, 55024

EMC radiated emission: DIN EN 61000-6-4, 55032

Mechanical stability: DIN EN 61373


Approvals and certifications

CE, DIN EN 60950-1, Listed UL 61010 (US/CA)

Status and diagnostic indicators

LED: Power | Link/Activity per Port

Drawing



Products

Article	Art.-No.	Specification
NITE-RW5-1190	111490	5xRJ45, IP30, FE, 24 V
NITE-RW8-1190	111690	8xRJ45, IP30, FE, 24 V
NITE-RW16-1190	111890	16xRJ45, IP30, FE, 24 V
NITE-RW5-1191	111491	5xRJ45, IP30, FE, 24 V, LLDP Blocking
NITE-RW8-1191	111691	8xRJ45, IP30, FE, 24 V, LLDP Blocking
NITE-RW16-1191	111891	16xRJ45, IP30, FE, 24 V, LLDP Blocking

Note: We reserve the right to make technical changes to this document without prior notice. TERZ assumes no responsibility or liability for any errors or inaccuracies in this document. All rights to this document and its contents are reserved. Duplication, use of the content or announcement to third parties in any form is not permitted without written permission from TERZ. Copyright © 2023 TERZ Industrial Electronics GmbH. All rights reserved.

TERZ Industrial Electronics GmbH
Gewerbepark 5a
D-49143 Bissendorf
Tel. +495402 60 80 970
Fax. +495402 60 80 979

020223
TZDS11149XEA_NITE-RW
www.terz-ie.com
info@terz-ie.com

