

NB1601-LSc

Industrial Router with LTE + 4x ETH + RS-232/485 + DIO

Modular mobile router with 4-port Ethernet switch to connect remote locations.



Keyfeatures

Mobile / Cellular	1x LTE, UMTS, GSM
SIM	2x Micro SIM
Ethernet	4x Fast Ethernet
IO	4x Digital I/O
Operation Temperature	-40°C to +70 °C
Serial / Fieldbus	1x RS-232/485, 1x RS-232 Console
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED)
Customizable	Extensions on request

Product description

The NB1601 offers the key technologies for stationary applications that require reliable Internet access.

Applications

- Condition Monitoring
- Remote Management
- Smart Buildings
- Environmental Monitoring
- Digital Signage
- Smart Grid
- Oil & Gas
- Renewable Energy
- Ticketing
- CCTV

Specifications

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Datarate down / up (max) 150 Mbps / 50 Mbps Voice CSFB FCC ID XPYTOBYL210
	Region Connectors SIM	Europe, Middle East and Africa (EMEA) 2x SMA female 2x Micro SIM - 3FF
Ethernet	Standard	4x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	4x RJ45
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A

Serial, Fieldbus	Protocol	<p>1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 1 Mbps</p> <p>1x RS-232/485 combo (software switchable) Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 1 Mbps</p> <p>Protocol EIA-485 Signals A, B Signal level Differential output voltage, loaded 1.5 VDC – 3.6 VDC Bit rate Up to 1 Mbps Termination 120 Ω for RS-485 configurable by software</p>
	Connector	2x Terminal block header 3.5 mm (screw locking)
IOs	Type	<p>2x Digital I/O Signals 1x DI, 1x DO DI signals +, - DI level Low: 0 - 3 VDC, high: 9 - 32 VDC DO signals Relay outputs with NO, NC, COM (normally open, normally closed) DO level 0 - 32 VDC/1A Isolation 1'500 VDC</p> <p>2x Digital I/O Signals 1x DI, 1x DO DI signals +, - DI level Low: 0 - 3 VDC, high: 9 - 32 VDC DO signals Relay outputs with NO, NC, COM (normally open, normally closed) DO level 0 - 32 VDC/1A Isolation 1'500 VDC Module COM-I/O shield</p>
	Connector	2x Terminal block header 3.5 mm (screw locking)
System	Core	600 MHz single core, 512 MB RAM, 4 GB flash
	Module Slots	1x miniPCIe / extension combo (USB), 1x Shield
Software	Features	<p>NetModule Router Software Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), logging Remote Management Manage and monitor devices with SNMP, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / soft-SIM support, multi-APN support, signal strength monitoring, dedicated bearers, GSM/CSFB calls Wireless LAN Client or Access Point mode, multi client support, multi / hidden SSID, WPA-PSK/WPA2-PSK, WPA-RADIUS, WPA-EAP-TLS, IEEE 802.11w, RADIUS accounting, CAPWAP Link Management Link prioritisation, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision Network Services DHCP Client, DNS server, email, SMS service, NTP Client, NTP server, DynDNS, SSH server, SNMP agent, HTTP/HTTPS/FTP server, voice gateway, SIP call routing, coovachilli hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, TCP-MSS clamping, STP/RSTP, bridging, LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, VLAN, PPPoE VPN OpenVPN, IPsec, PPTP, GRE, CSD dial-in Firewall Stateful firewall, connection tracking, NAT, masquerading, bridge filtering</p>
Power	Input Voltage	<p>12, 24 VDC Nominal voltages 12, 24 VDC Absolute voltages 12 VDC to 24 VDC (-20 % / +20 %)</p>
	Connector	1x Terminal block header 3.5 mm (screw locking)
	Consumption	7 W (average), 10 W (max)
Mounting		DIN-Rail
Dimensions	W x H x D	Width 45 mm x height 124/134 mm x depth 110/121 mm
Weight		450 g
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP40
MTBF		300'000 h / 34.2 years, according SN29500 at environmental temperature 40 °C

Certifications**Compliance
Domain**CE according to 2014/53/EU (RED), 2011/65/EU (RoHS)
Industrial

Order Code

NB1601-LSc