

NB800-LWWtSu-GE

Fahrzeug-Router mit LTE + WLAN + BT/BLE + ETH + USB + GNSS + E-Mark

Kompakter, modularer Mobilfunk-Router zur Vernetzung von Spezialfahrzeugen.



Hauptmerkmale

Mobilfunk	1x LTE, UMTS, GSM
SIM	1x Micro SIM / 1x eSIM Chip (auf Anfrage)
WiFi / WLAN	1x Dual-band IEEE 802.11a/b/g/n (Wi-Fi 4), 1x Bluetooth Low Energy
Ethernet	1x Fast Ethernet
Ortung	Multi-GNSS
USB	USB 2.0 Host
Betriebstemperatur	-40 °C bis +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, freie Updates
Konformität	CE (RED), Fahrzeug (UNECE-R10, UNECE-R118)
Modularität	Erweiterungen auf Anfrage

Produktbeschreibung

Der kompakte NB800 ist die kostengünstige Lösung für eine robuste bordeigene Internetverbindung in Fahrzeugen.

Anwendungen

- [Blaulichtorganisationen](#)
- [Intelligenter Verkehr](#)
- [Flottenmanagement](#)
- [Passagier-Infotainment](#)
- [Kommunikation](#)
- [Telematik](#)
- [Nachverfolgung](#)

Spezifikation

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB FCC ID XPYTOBYL210
	Region Connectors SIM	Europe, Middle East and Africa (EMEA) 2x SMA female 1x Micro SIM - 3FF / eSIM Chip (auf Anfrage)
WiFi / WLAN	Standard	1x Dual-band WLAN 2.4/5 GHz a/b/g/n (Wi-Fi 4) + BT 4.2 combo Wireless standard IEEE 802.11a/b/g/n (Wi-Fi 4) Bluetooth 4.2, Bluetooth Low Energy Frequency 2.4/5 GHz Antenna ports 2x2 MIMO Data rate (max) 144 Mbps 2.4 GHz 2x2 MIMO, 150 Mbps 5 GHz SISO Modes Client or access point (up to 10 clients) FCC ID Z64-WL18DBMOD
	Connector	2x SMA female
Ethernet	Standard	1x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	1x RJ45

Positioning	Standard	1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream
	Connector	1x SMA female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
System	Core	1 GHz single core, 512 MB RAM, 4 GB flash, HW Rev. B02
	Module Slots	1x Shield
Software	Features	NetModule Router Software Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), logging Remote Management Manage and monitor devices with SNMP, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / soft-SIM support, multi-APN support, signal strength monitoring, dedicated bearers, GSM/CSFB calls Wireless LAN Client or Access Point mode, multi client support, multi / hidden SSID, WPA-PSK/WPA2-PSK, WPA-RADIUS, WPA-EAP-TLS, IEEE 802.11w, RADIUS accounting, CAPWAP Link Management Link prioritisation, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision Network Services DHCP Client, DNS server, email, SMS service, NTP Client, NTP server, DynDNS, SSH server, SNMP agent, HTTP/HTTPS/FTP server, voice gateway, SIP call routing, coovachilli hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, TCP-MSS clamping, STP/RSTP, bridging, LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, VLAN, PPPoE VPN OpenVPN, IPsec, PPTP, GRE, CSD dial-in Firewall Stateful firewall, connection tracking, NAT, masquerading, bridge filtering
	Licenses	GNSS Enabled service GNSS location service Server with JSON-, NMEA stream
Power	Input Voltage	12, 24 VDC Nominal voltages 12, 24 VDC Absolute voltages 12 VDC to 24 VDC (-20 % / +20 %)
	Connector Consumption	1x Terminal block header 3.5 mm 5 W (average), 10 W (max)
Mounting		Bracket
Dimensions	W x H x D	Width 85/111 mm x height 32 mm x depth 110 mm
Weight		220 g
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP40
MTBF		340'000 h / 38.8 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Vehicle according to UNECE-R10, UNECE-R118 Vehicle
Order Code		NB800-LWWtSu-GE