

NB2800-4L-GV

Fahrzeug-Router mit 4x LTE + 2x GbE + GNSS + Voice + E-Mark

Leistungstarker und modularer Mobilfunk-Router für drahtlosen Internetzugang im Fahrzeug.



Hauptmerkmale

Mobilfunk	4x LTE, UMTS, GSM
SIM	4x Micro SIM
Ethernet	2x Gigabit Ethernet
Sprachkommunikation	Voice Gateway (max. 3 gleichzeitige Anrufe)
Speisung	12 VDC bis 48 VDC, Zündungserkennung
Ortung	Multi-GNSS
Betriebstemperatur	-25 °C bis +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, freie Updates
Konformität	CE (RED), Fahrzeug (UNECE-R10, UNECE-R118), ITxPT optional
Modularität	Erweiterungen auf Anfrage

Produktbeschreibung

Der NB2800 bietet drahtlosen Internetzugang im Fahrzeug.

Anwendungen

- Flottenmanagement
- Passagier-Infotainment
- Fahrkartensysteme
- Telematik
- Kommunikation
- Blaulichtorganisationen

Spezifikation

Mobile / Cellular	Standard	4x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB FCC ID XPTYOBYL210
	Region Connectors SIM	Europe, Middle East and Africa (EMEA) 8x FAKRA D-coded male 4x Micro SIM - 3FF
Ethernet	Standard	2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps
	Connector	2x RJ45
Positioning	Standard	1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream
	Connector	1x FAKRA C-coded male

USB	Standard Connector	1x USB 3.0 Host 1x Type A
Serial, Fieldbus	Protocol	1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 1 Mbps
	Connector	1x Terminal block header 5 mm
System	Core Module Slots	1.3 GHz dual core, 1 GB RAM, 4 GB flash 2x miniPCIe (PCIe + USB), 2x miniPCIe (USB)
Software	Features	NetModule Router Software Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), logging Remote Management Manage and monitor devices with SNMP, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / soft-SIM support, multi-APN support, signal strength monitoring, dedicated bearers, GSM/CSFB calls Wireless LAN Client or Access Point mode, multi client support, multi / hidden SSID, WPA-PSK/WPA2-PSK, WPA-RADIUS, WPA-EAP-TLS, IEEE 802.11w, RADIUS accounting, CAPWAP Link Management Link prioritisation, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision Network Services DHCP Client, DNS server, email, SMS service, NTP Client, NTP server, DynDNS, SSH server, SNMP agent, HTTP/HTTPS/FTP server, voice gateway, SIP call routing, coovachilli hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, TCP-MSS clamping, STP/RSTP, bridging, LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, VLAN, PPPoE VPN OpenVPN, IPsec, PPTP, GRE, CSD dial-in Firewall Stateful firewall, connection tracking, NAT, masquerading, bridge filtering
	Licenses	GNSS, Enabled service GNSS location service Server with JSON-, NMEA stream Voice gateway Enabled service Versatile voice gateway for seamless call routing Protocols 2G/3G/4G, POTS, VoIP, PTT (if supported by hardware)
Power	Input Voltage	12, 24, 48 VDC Nominal voltages 12, 24, 48 VDC Absolute voltages 12 VDC to 48 VDC (-25 % / +20 %) Ignition sense Input with delayed shutdown
	Ignition Sense Connector Consumption	Ja 1x Terminal block header 5 mm 20 W (max)
Mounting		Bracket
Dimensions	W x H x D	Width 164/190 mm x height 58 mm x depth 139.5 mm
Weight		1200 g
Environment	Operating Temperature Ingress Protection Level	-25°C to +70°C IP40
MTBF		200'000 h / 22.8 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), Vehicle according to UNECE-R10, UNECE-R118 Vehicle
Order Code		NB2800-4L-GV