



COMPACT FANLESS EMBEDDED SYSTEMS

RCO-1000-EHL-20

Compact fanless embedded system with Intel Atom® CPU, 2x DP, 2x COM, 1x 2.5" SATA HDD Bay

Features

- Support Intel Atom® Processor
- 1x 260-pin DDR4 SODIMM. Max. up to 32GB
- Dual Independent Display by 2x Display Port
- 1x 2.5GbE, 1x GbE supporting (Wake-on-LAN and PXE)
- 1x 2.5" SATA HDD Bay, 1x mSATA,
- 1x M.2 (B Key, 2242/3042/3052, Support 4G/5G)
- 1x Full-size mini PCIe for communication or expansion modules
- 2x RS-232/422/485, 3x USB 3.2 Gen2, 1x USB 2.0
- 9 to 36VDC Wide Range Power Input Supporting AT/ATX Mode
- Wide Operating Temperature -40°C up to 70°C
- TPM 2.0 Supported
- With 3x Universal Expansion Slots
- UL Listed



Specifications


System		Power Protection	OVP (Over Voltage Protection); OCP (Over Current Protection) Reverse Protection
Processor		Environment	
Supports 11th Gen Intel® Atom® Processor (Elkhart Lake) - Intel® Atom® Processor X6425E, Quad Core, 1.5 MB Cache, 2.0 GHz, 12W TDP			
System Chipset	SoC integrated	Operating Temperature	-40°C to 70°C (Supported by Intel® Embedded Series: x6425E)
LAN Chipset	1 GbE1: Intel I210 (Support Wake-on-LAN and PXE) 2.5 GbE2: Intel I225 (Support Wake-on-LAN and PXE)	Storage Temperature	-40°C to 85°C
Audio Codec	Realtek ALC888S	Relative Humidity	10% to 95% (non-condensing)
System Memory	1x 260-Pin DDR4 2400/2667/3200MT/s SODIMM. Max. up to 32 GB	Certification	UL 62368 Ed. 3, CE, FCC Class A
Graphics	Intel® UHD Graphics	Vibration	With SSD: 5 Grms, 5 - 500 Hz, 0.5 hr/axis With HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis
BIOS	AMI 256Mbit SPI BIOS	Shock	With SSD: 50G, half sine, 11ms
Watchdog	Software Programmable Supports 1~255 sec. System Reset	Physical	
TPM	TPM 2.0		
Display		Dimensions	150 (W) x 105 (D) x 65 (H) mm
Display Port	2x DisplayPort 1.4, DP++ (4096 x 2160@60Hz)	Weights	1 kg
Multiple Display	Dual Display	Construction	Extruded Aluminum with Heavy Duty Metal
Storage		Mounting Options	Wall Mounting SIDE / VESA / DIN-Rail Mounting (Optional)
M.2	1x M.2 (B Key, 2242/3042/3052, PCIe1 + USB 3.2 Gen2, Support 4G/5G Module)		
mSATA	1x mSATA (shared by 1x Mini PCI Express)		
SIM Socket	2x External SIM socket		
SSD/HDD	1x Internal 2.5" SATA HDD Bay (support H=9.5 mm)		
Expansion			
Mini PCIe	1x Full-size Mini PCIe		
Expansion Modules			
Optional:			
• 2-port COM module with Super I/O Chipset, Support 2x Universal Slot Only			
• 4-Port USB module with USB hub, Support 1x Universal Slot Only			
• 1-Port DP 1.4 and DIO (4 in / 4 out, Isolated), Support 1x Universal Slot Only			
• 1-Port HDMI 2.0, Support 1x Universal Slot Only			
I/O			
Audio	1x Mic-in, 1x Line-out		
CAN	2x CAN 2.0 A/B 2-pin Internal header		
COM	2x RS-232/422/485		
LAN	2x RJ45 (2.5 & 1 GbE)		
Universal I/O Bracket	3x Universal I/O Bracket (By mini PCIe interface, C&T Proprietary Module)		
USB	3x USB 3.2 Gen 2 (10 Gbps) 1x USB 2.0		
Others	5x WiFi Antenna Holes 1x Power Switch, 1x AT/ATX Switch, 1x Remote Power On/Off 1x Internal CMOS Battery Cable 1x 4-PIN FAN Connector		
Operating System			
Windows	Windows 10		
Linux	Linux Kernel		
Power			
Power Adapter	Optional AC/DC 12V/5A, 60W		
Power Mode	AT, ATX		
Power Ignition Sensing	Adjustable power ignition management can be achieved through BIOS and optional daughter board.		
Power Supply Voltage	9~36VDC		
Power Connector	3-pin Terminal Block		

* For configured to run at 12W, operating temperatures will be limited to 70°C.


** 12W CPUS may experience thermal throttling depending on extreme application workloads; this is also due to an increase in the physical CPU cores from the Intel silicon (up to 4 cores). Please note, this does not indicate

* For configured to run at 12W, operating temperatures will be limited to 70°C.
** 12W CPUS may experience thermal throttling depending on extreme application workloads; this is also due to an increase in the physical CPU cores from the Intel silicon (up to 4 cores). Please note, this does not indicate system malfunction or problems in the fanless design. Please consult our embedded engineers for the best configuration to match your application requirements.
*** All specifications and photos are subject to change without notice.

External I/O Mechanical Layout




Available Expansion Module Options for Rear Panel



Dimension

Unit: mm



Available Models

Model No.	Description
RCO-1000-EHL-X6425E-20C	Compact fanless embedded system with Intel x6425E CPU, 3x DP, 4x COM, DIO, 1x 2.5" SATA HDD Bay
RCO-1000-EHL-X6425E-20D	Compact fanless embedded system with Intel x6425E CPU, 2x DP, 6x COM, 1x 2.5" SATA HDD Bay

Optional Accessories

Model No.	Description
1-E09A06008	Adapter AC/DC 12V 5A 60W with 3pin Terminal Block Plug 5.0mm Pitch
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm
1-TPCD00005	Power Cord, 3-pin US Type, 180cm
3-SIDE-0003	RCO-1000-EHL-20 Series Side Mount Kit
3-VESA-0003	RCO-1000 Series VESA Mount Kit
3-DINR-0004	Din Rail-2 Mounting Kit

Packing List

1x RCO-1000-EHL-20 Series Embedded System
1x Wall Mount Kit
1x Accessory Kit