

Product Discontinuance Notification—PDN# 0000411614

August 01, 2024

Dear Valued Customer,

We would like to inform you that Moxa is going to discontinue the EDS-P510 Series. This process will effectively begin August 01, 2024.

If you need any of these discontinued products for an existing project, please contact your Moxa sales representative to place orders before February 03, 2025. Also, please note that last-buy orders may be subject to availability.

Please review the details below to determine how these discontinuances will affect your products and/or operations.

Which products will be discontinued?

The following products will be discontinued. Also, see the models recommended to replace the soon to-be-discontinued models, as well as when the replacement models will be available for order.

Discontinued	Recommended Replacement	Available for Order
EDS-P510 Series	EDS-P510A Series	Available Now
(EDS-P510, EDS-P510-T, EDS-P510-T (CV-CT))	SDS-3010 Series	October, 2024

Applicable differences in specifications

In this table, we list the difference in specifications between the discontinued products and the recommended replacement products.

Specification	EDS-P510 Series (Discontinued)	EDS-P510A Series (Replacement)
Product Category	L2 Managed Switch	L2 Managed Switch
Dimensions	80.2 x 135 x 105 mm	79.2 x 135 x 105 mm
Operating Temperature	0 to 60°C (32 to 140°F)	-10 to 60°C (14 to 140°F)
Ethernet Interface	3 Combo Ports (10/100/1000BaseT(X) or 1000BaseSFP) 4 PoE Ports (10/100BaseT(X), RJ45 connector) 3 Non-PoE Ports (10/100BaseT(X), RJ45 connector)	2 Combo Ports (10/100/1000BaseT(X) or 1000BaseSFP) 8 PoE Ports (10/100BaseT(X), RJ45 connector) 0 Non-PoE Ports (10/100BaseT(X), RJ45 connector)

Power Over Ethernet	IEEE 802.3af Total Power Budget (Max.): 61.6 W Each PoE Port (Max.): 15.4 W	IEEE 802.3af/ at Total Power Budget (Max.): 240 W Each PoE Port (Max.): 36 W
Certification	UL 508, EN 62368-1, Marine (ABS, DNV, LR, NK)	UL 508, Hazardous Locations (CID2), Traffic Control (NEMA TS2)

Specification	EDS-P510 Series (Discontinued)	SDS-3010 Series (Replacement)
Product Category	L2 Managed Switch	L2 Smart Switch
Dimensions	80.2 x 135 x 105 mm	36 x 135 x 111 mm
Operating Temperature	0 to 60°C (32 to 140°F)	-10 to 60°C (14 to 140°F)
Ethernet Interface	3 Combo Ports (10/100/1000BaseT(X) or 1000BaseSFP) 4 PoE Ports (10/100BaseT(X), RJ45 connector) 3 Non-PoE Ports (10/100BaseT(X), RJ45 connector)	2 Combo Ports (10/100/1000BaseT(X) or 1000BaseSFP) 8 PoE Ports (10/100BaseT(X), RJ45 connector) 0 Non-PoE Ports (10/100BaseT(X), RJ45 connector)
Power Over Ethernet	IEEE 802.3af Total Power Budget (Max.): 61.6 W Each PoE Port (Max.): 15.4 W	IEEE 802.3af/ at Total Power Budget (Max.): 240 W Each PoE Port (Max.): 36 W
Certification	UL 508, EN 62368-1, Marine (ABS, DNV, LR, NK)	UL 61010-2-201, EN 62368-1

For more PoE product options, please visit Moxa's website at

<https://www.moxa.com/en/products/industrial-network-infrastructure/ethernet-switches/poe-switches>.

Please note that all service rules (e.g., warranty) still apply to discontinued products.

If you have any questions, please contact Hazel Chiang at HazelCI.Chiang@moxa.com, or contact your regional sales representative.